



Safety Data Sheet

**24 Hour Emergency Phone Numbers
Medical/Poison Control:**
In U.S.: Call 1-800-222-1222

**Outside U.S.: Call your local poison
control center**

**Transportation/National Response
Center:**

**1-800-535-5053
1-352-323-3500**

NOTE: The National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.

IMPORTANT: Provide this information to employees, customers, and users of this product. Read this SDS before handling or disposing of this product. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard. All abbreviated terms used in this SDS are further described in Section 16.

1. Identification

This Safety Data Sheet is available in American Spanish upon request.
Los Datos de Seguridad pueden obtenerse en Espanol si lo requiere.

Product Name:	Gutter & Flashing Butyl Flex Rubber Sealant	Revision Date:	4/11/2022
Product UPC Number:	070798737518	Supercedes Date:	New SDS
Product Use/Class:	Caulking Compound	SDS No:	1701465
Manufacturer:	DAP Global Inc. 2400 Boston Street Suite 200 Baltimore, MD 21224-4723 888-327-8477 (non - emergency matters)	Imported by:	DAP Canada 475 Finchdene Square Unit 5 Scarborough, Ontario M1X 1B7 888-327-8477 (non - emergency matters)
	SDS Coordinator: MSDS@dap.com		SDS Coordinator: MSDS@dap.com
	Emergency Telephone: 1-800-535-5053, 1-352-323-3500, 1-800-222-1222		Emergency Telephone: 1-800-535-5053, 1-352-323-3500

Preparer: Regulatory and Environmental Affairs

2. Hazards Identification

GHS Classification

Flam. Liq. 3, STOT RE 1

Symbol(s) of Product**Signal Word**

Danger

Possible Hazards

50% of the mixture consists of ingredients of unknown acute toxicity

GHS HAZARD STATEMENTS

Flammable Liquid, category 3	H226	Flammable liquid and vapour.
STOT, repeated exposure, category 1	H372	Causes damage to organs through prolonged or repeated exposure.

GHS LABEL PRECAUTIONARY STATEMENTS

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P314	Get medical advice/attention if you feel unwell.
P370+P378	In case of fire: Use... to extinguish.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container.

GHS SDS PRECAUTIONARY STATEMENTS

P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/.../ equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P270	Do not eat, drink or smoke when using this product.

3. Composition/Information on Ingredients

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. %</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
Stoddard solvent	8052-41-3	10-30	GHS08	H304-372
Magnesite	546-93-0	3-7	No Information	No Information

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

4. First-aid Measures

FIRST AID - INHALATION: If inhaled, remove to fresh air. If breathing is difficult, leave the area to obtain fresh air. If continued breathing difficulty is experienced, get medical attention immediately. NOTE: Only trained personnel should administer artificial respiration or give oxygen.

FIRST AID - SKIN CONTACT: Wash skin with soap and water for 15 minutes. Get medical aid if symptoms persist. Remove and wash contaminated clothing.

FIRST AID - EYE CONTACT: If material gets into eyes, flush with water immediately for 15 minutes. Consult a physician.

FIRST AID - INGESTION: If swallowed, DO NOT INDUCE VOMITING. Get medical attention immediately.

5. Fire-fighting Measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: Eliminate sources of ignition: heat, electrical equipment, sparks and flames. Vapors can form an ignitable mixture with air. Vapors can flow along surfaces to a distant ignition source and flash back. Vapors may form explosive mixtures with air. Containers may explode if exposed to extreme heat. Empty containers retain product residue (liquid and/or vapor). Vapor can ignite potentially causing an explosion.

SPECIAL FIREFIGHTING PROCEDURES: Wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear. Use water spray to cool exposed surfaces.

EXTINGUISHING MEDIA: Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Spray or Fog, Water

6. Accidental Release Measures

ENVIRONMENTAL MEASURES: No Information

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: NOTE: Review fire hazards before proceeding with clean up. Immediately eliminate sources of ignition. Keep people away from and upwind of spill/leak. Prevent product from entering drains. Soak up with inert absorbent material and dispose of as hazardous waste. Read all product instructions before using. Personal protective equipment should include impervious gloves, protective eye wear, and suitable work clothes. Scrape up dried material and place into containers.

7. Handling and Storage

HANDLING: KEEP OUT OF REACH OF CHILDREN! DO NOT TAKE INTERNALLY. Remove all sources of ignition. Keep away from open flames, hot surfaces and sources of ignition. Provide adequate ventilation. Avoid heat, sparks and open flames. Wear appropriate personal protection. Avoid breathing vapor and contact with eyes, skin and clothing. Use in well ventilated area. Open all windows and doors or use other means to ensure cross-ventilation and fresh air entry during application and drying. Odor is not an adequate warning for hazardous conditions. Empty containers retain product residue (liquid and/or vapor). Vapor can ignite potentially causing an explosion. Wash thoroughly after handling. Do not use in areas where static sparks may be generated.

STORAGE: Store away from sources of ignition and heat. Do not store at temperatures above 120 °F (49 °C). Store containers away from excessive heat and freezing. Store away from caustics and oxidizers. Keep containers tightly closed.

8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH-TLV STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>
Stoddard solvent	100 ppm TWA	N.E.	500 ppm TWA, 2900 mg/m ³ TWA	N.E.
Magnesite	N.E.	N.E.	N.E.	N.E.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation
Sk = Skin Sensitizer N.E. = Not Established

Personal Protection



RESPIRATORY PROTECTION: A NIOSH-approved air purifying respirator with an organic vapor cartridge or canister may be necessary under certain circumstances where airborne concentrations are expected to exceed exposure limits. If concentrations exceed the exposure limits specified, use of a NIOSH-approved supplied air respirator is recommended. Where the protection factor is exceeded, use of a Self Contained Breathing Apparatus (SCBA) may be necessary. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear and appropriate, properly fitted respirator (NIOSH approved) during and after application. A respiratory protection program that meets the OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.



SKIN PROTECTION: Solvent-resistant gloves.



EYE PROTECTION: Goggles or safety glasses with side shields.



OTHER PROTECTIVE EQUIPMENT: Provide eyewash and solvent impervious apron if body contact may occur.



HYGIENIC PRACTICES: Remove and wash contaminated clothing before re-use.

9. Physical and Chemical Properties

Appearance:	White to Off-White	Physical State:	Paste
Odor:	Strong Solvent	Odor Threshold:	Not Established
Density, g/cm³:	1.40 - 1.40	pH:	Not Applicable
Freeze Point, °C:	Not Established	Viscosity (mPa.s):	Not Established
Solubility in Water:	Not Established	Partition Coeff., n-octanol/water:	Not Established
Decomposition Temperature, °C:	Not Established	Explosive Limits, %:	N.E. - N.E.
Boiling Range, °C:	N.A. - N.A.	Auto-Ignition Temperature, °C	Not Established
Minimum Flash Point, °C:	36.7	Vapor Pressure, mmHg:	Not Established
Evaporation Rate:	Not Established	Flash Method:	Pensky-Martens Closed Cup
Vapor Density:	Heavier Than Air	Flammability, NFPA:	Flammable Liquid Class IC
Combustible Dust:	Does not support combustion		

(See "Other information" Section for abbreviation legend)

(If product is an aerosol, the flash point stated above is that of the propellant.)

10. Stability and Reactivity

STABILITY: Stable under normal conditions.

CONDITIONS TO AVOID: Keep away from open flames, hot surfaces and sources of ignition. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. Do not smoke.

INCOMPATIBILITY: Open flames, hot surfaces and sources of ignition. Keep away from strong oxidizing agents, heat and open flames. Strong acids and strong bases.

HAZARDOUS DECOMPOSITION PRODUCTS: Normal decomposition products, i.e., CO_x, NO_x.

11. Toxicological Information

EFFECT OF OVEREXPOSURE - INHALATION: Inhalation of vapors may cause irritation of the nose, throat, lungs and respiratory tract. Inhalation of vapors in high concentration may cause shortness of breath (lung edema). Prolonged, repeated or high exposures may cause central nervous system depression leading to headaches, nausea, drowsiness, dizziness, and possibly narcosis. In extreme cases, may cause loss of consciousness.

EFFECT OF OVEREXPOSURE - SKIN CONTACT: May cause skin irritation. Prolonged and repeated skin contact may cause dermatitis, drying and defatting due to the solvent properties.

EFFECT OF OVEREXPOSURE - EYE CONTACT: May cause eye irritation.

EFFECT OF OVEREXPOSURE - INGESTION: Harmful or fatal if swallowed. May cause gastrointestinal disturbances with dizziness and central nervous system depression. If ingested, may cause depressed respiration. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

CARCINOGENICITY: No Information

EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS: Prolonged or repeated contact with skin can cause defatting of the skin, which may lead to dermatitis. Prolonged or repeated inhalation of solvent vapors may cause irregular heartbeat. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Symptoms include: loss of memory, loss of intellectual ability and loss of coordination. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Constituents of this product include crystalline silica which, if inhalable, may cause silicosis, a form of progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a known human carcinogen. Constituents may also contain asbestiform or non-asbestiform tremolite or other silicates as impurities, and above de minimus exposure to these impurities in inhalable form may be carcinogenic or cause other serious lung problems.

PRIMARY ROUTE(S) OF ENTRY: Skin Contact, Skin Absorption, Inhalation

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
8052-41-3	Stoddard solvent	>7000 mg/kg Rat	>2000 mg/kg Rabbit	21 mg/L Rat

546-93-0 Magnesite

>2000 mg/kg Rat N.I.

N.I.

N.I. = No Information

12. Ecological Information

ECOLOGICAL INFORMATION: Ecological injuries are not known or expected under normal use.

13. Disposal Information

DISPOSAL INFORMATION: Residues and spilled material are hazardous waste due to ignitability. Dispose of material in accordance with all federal, state and local regulations. State and Local regulations/restrictions are complex and may differ from Federal regulations. Responsibility for proper waste disposal is with the owner of the waste. Liquids cannot be disposed of in a landfill. Do not flush into surface water or sanitary sewer system. Do not empty into drains. Do not re-use empty containers. The container for this product can present explosion or fire hazards, even when emptied. To avoid risk of injury, do not cut, puncture, or weld on or near this container.

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: NOTE: Review fire hazards before proceeding with clean up. Immediately eliminate sources of ignition. Keep people away from and upwind of spill/leak. Prevent product from entering drains. Soak up with inert absorbent material and dispose of as hazardous waste. Read all product instructions before using. Personal protective equipment should include impervious gloves, protective eye wear, and suitable work clothes. Scrape up dried material and place into containers.

14. Transport Information

SPECIAL TRANSPORT PRECAUTIONS: No Information

DOT UN/NA Number:	UN1133
DOT Proper Shipping Name:	Adhesives, containing a flammable liquid
DOT Technical Name:	N.A.
DOT Hazard Class:	3 Flammable liquid
Hazard SubClass:	N.A.
Packing Group:	III

15. Regulatory Information

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

TOXIC SUBSTANCES CONTROL ACT:

All ingredients in this product are either on TSCA inventory list, or otherwise exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

16. Other Information

Revision Date: 4/11/2022 **Supersedes Date:** New MSDS

Reason for revision: HazCom2012/GHS Conversion

Datasheet produced by: Regulatory Department

HMIS Ratings:

Health:	Flammability:	Reactivity:	Personal Protection:
2*	3	0	X

VOC Less Water Less Exempt Solvent, g/L: 210.0

VOC Material, g/L: 210

VOC as Defined by California Consumer Product Regulation, Wt/Wt%: 15.00

VOC Actual, Wt/Wt%: 15.0

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H304 May be fatal if swallowed and enters airways.
 H372 Causes damage to organs through prolonged or repeated exposure.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:

GHS08



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

DAP believes the data and statements contained herein are accurate as of the date hereof. They are offered in good faith as typical values and not as a product specification. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE WITH REGARD TO THE INFORMATION HEREIN PROVIDED OR THE PRODUCT TO WHICH THE INFORMATION REFERS. Since this document is intended only as a guide to the appropriate use and precautionary handling of the referenced product by a properly trained person, it is therefore the responsibility of the user to (i) review the recommendations with due consideration for the specific context of the intended use and (ii) determine if they are appropriate.