



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® Textured Mortar Premium Elastomeric Latex Filler & Sealant

PRODUCT DESCRIPTION

DAP® Textured Mortar is a high performing acrylic latex filler & sealant used for repairing and sealing cracks and joints in mortar, masonry, concrete, stone, and brick. The textured finish blends easily with most mortar substrates for a seamless finish. It has excellent flexibility, adhesion, and durability providing a long-lasting seal. Easy water cleanup, low odour & won't stain or bleed onto the application surface. Exterior / Interior Use.



FPO

PACKAGING	COLOUR	SKU	UPC
300mL (10.1 fl oz) Cartridge	Textured Beige	7079870081	0 7079870081 9
300mL (10.1 fl oz) Cartridge	Textured Gray	7079870082	0 7079870082 6

KEY FEATURES & BENEFITS

- Fills and seals cracks and holes in mortar surfaces
- Fills gaps and cracks up to 7.62 cm (3") wide
- Meets ASTM C920, Class 25
- Provides a durable, long-lasting seal, backed by a Lifetime Guarantee
- Cured sealant is mould and mildew resistant
- 100% waterproof & weatherproof seal
- Excellent adhesion & flexibility for a durable seal
- Textured to blend with mortar & masonry surfaces
- Easy water clean-up & low odour
- Won't stain or bleed
- 2-hour paint ready
- Exterior/Interior



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

SUGGESTED USES

FILLING & SEALING CRACKS & GAPS IN:

- Mortar
- Brick
- Patios
- Steps
- Above ground foundations
- Concrete surfaces
- Stucco
- Sidewalks
- Garage floors
- Pavements

ADHERES TO:

- Mortar
- Concrete
- Brick
- Stone
- Cinderblock
- Stucco
- Wood
- Most metals

FOR BEST RESULTS

- Apply in temperatures above 4.4°C (40°F). Do not apply when rain or freezing temperatures are forecasted.
- Not for continuous underwater use.
- Joint size should not exceed 7.5 cm (3") wide by 1.27 cm (1/2") deep. If joint exceeds 1.27 cm (1/2"), use foam backer rod. Allow to cure 24 hours before direct exposure to water.
- Serviceable for pedestrian & vehicular traffic after 24 hours (minimum).
- Fully cures in 2-4 days, depending on temperature, humidity & depth of fill.
- Store sealant away from extreme heat or cold.

APPLICATION

Surface Preparation

Surface must be clean, dry, structurally sound and free of all foreign material.

Product Application

1. Apply in temperatures above 4.4°C (40°F). Do not apply when rain or freezing temperatures are forecasted within 24 hours. Cooler temperatures and higher humidity will slow down dry time.
2. Cut nozzle at 45° angle to desired bead size.
3. Load cartridge into caulk gun.
4. Fill cracks and gaps with sealant.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

5. After application, a more uniform fill or neater appearance may be obtained by lightly misting a trowel or putty knife with water and tooling sealant lightly.
6. Allow to cure 24 hours before direct exposure to water (longer in cooler and/or humid conditions).
7. Paintable after 2 hours (longer in cool or humid conditions) with latex or oil-based paints.
8. Clean up excess wet sealant with a damp sponge before it skins over (within 30 minutes).
9. Excess dried sealant will need to be cut or scraped away.
10. Reseal cartridge for future use. Store away from extreme heat or cold.

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Typical Uncured Physical Properties	
Appearance/Consistency	Textured
Base Polymer:	Acrylic Latex
Filler:	Calcium carbonate
Volatile:	Water
Weight % Solids	79% by weight
Specific gravity	1.3
Odour	Very mild
Clean Up	Water
Flash Point	>100°C (212°F)
Freeze Thaw Stability:	Passes 5 Cycles
Shelf Life	12 months
Coverage	15 linear meters (55 linear feet) at 5 mm (3/16") diameter bead
Typical Application Properties	
Application Temperature Range:	4.4°C to 37.8°C (40°F to 100°F)
Tooling Time (Working Time)	10 minutes
Tack Free Time	30 minutes
Return to Service Time	24 hrs
Full Cure Time	2 – 4 days
Vertical Sag (D2202)	1.3 mm
Typical Cured Performance Properties	
Service Temperature Range:	-34.4°C to 82.2°C (-30°F to 180°F)
Paint Ready Time	2 Hours
Water Ready Time	24 hours



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

CLEAN UP & STORAGE

Clean up excess wet caulk with a damp sponge before it skins over (within 30 minutes). Excess dried caulk must be cut or scraped away. Clean hands and tools with warm, soapy water. Store in a cool, dry place away from extreme heat or cold.

SAFETY

See product label or Safety Data Sheet (SDS) for health and safety information. You can request a SDS by visiting our website at dap.ca or calling 888-DAP-TIPS.

WARRANTY

DAP Canada will not accept liability for more than replacement product or sales price refund under any circumstances.

COMPANY IDENTIFICATION

Manufactured for: DAP Canada, 475 Finchdene Square, Unit 5, Scarborough, ON, M1X 1B7

Usage Information: Call 888-DAP-TIPS or visit dap.ca & click on "Ask the Expert"

Order Information: 800-668-9397 or 416-321-1522

Fax Number: 416-321-3325

Also visit the DAP website at dap.ca