



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® CONSTRUCTION ADHESIVE Tub Surround

PRODUCT DESCRIPTION

DAP® CONSTRUCTION ADHESIVE Tub Surround construction adhesive is a premium grade, high strength adhesive specifically formulated for tub surround installation. This premium adhesive is safe for use on all tub surround materials and dries clear for an ideal finish. CONSTRUCTION ADHESIVE Tub Surround is an instant grab adhesive that is moisture, steam, water, and heat resistance once fully cured.



PACKAGING	COLOUR	UPC
305 mL (10.3 fl. oz.) Cartridge	White	7079874885

KEY FEATURES & BENEFITS

- Shower Safe - Safe to use on all tub surround and shower enclosure materials
- Dries Clear for an Ideal Finish - Goes on white and dries clear for an ideal finish
- Stronger Holding Power* – Powerful adhesion to hold panels in place

*Stronger than competitive tub surround adhesives

PERFORMANCE CHARACTERISTICS

- Won't etch or burn tub surround material
- Instant grab
- Easy water clean up
- VOC compliant



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

SUGGESTED USES

Adheres to:

- ABS Tub Surrounds
- Acrylic Tub Surrounds
- Cement Backerboard
- Ceramic Tiles
- Dimensional Lumber
- Drywall
- Fiberglass Tub Surrounds
- Foamback Tub Surrounds
- Greenboard
- OSB
- Plywood
- PVC Tub Surrounds

Recommended for:

- Tub Surround Installation
- Shower Wall Enclosures

Not Recommended for:

- Mirror installation
- Bonding two non-porous materials
- Applications other than tub surround & water enclosure installation

FOR BEST RESULTS

- Apply in temperatures above 4.4°C. Keep adhesive above 4.4°C for easier gunning.
- One surface must be porous.
- Store away from extreme heat or cold

APPLICATION

1. Surfaces must be clean, structurally sound, and free of debris.
2. Pre-cut and fit materials before applying adhesive.
3. Trim nozzle to desired bead size. 6 mm (1/4") recommended for most applications.
4. Puncture inner foil seal.
5. Load cartridge into applicator gun.
6. Apply a continuous bead to studs or backer substrate, adhesive may also be applied to back of tub surround panel according to tub surround manufacturers installation instructions.
7. Within 10 minutes, position and press panels firmly into place.
8. Allow to dry for 24 hours before exposing to water or moisture.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Typical Uncured Physical Properties	
Appearance/Consistency	Smooth paste
Base Polymer:	Synthetic latex
Bead Colour	White
Weight % Solids	51%
Odour	Mild
Clean Up	Soap & water
Flash Point	100°C
Shelf Life	18 months
Coverage	305 ml (10oz): 6 mm (¼") bead yields 10 linear meters (32 linear ft), 9.5 mm (3/8") bead yields 4 linear meters (14 linear ft)
Typical Application Properties	
Application Temperature Range:	4.4°C – 37.7°C
Tooling Time (Working Time)	20 minutes
Full Cure Time	7 days
Typical Cured Performance Properties	
Service Temperature Range:	-18°C – 60°C
Gap Bridging	N/A
VOC Content	< 50g/L

CLEAN UP & STORAGE

Uncured adhesive: wash away with warm water and soap. Cured adhesive: must be cut or scraped away.

SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.ca or by calling **888-DAP-TIPS**.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

WARRANTY

DAP Canada, DAP Products Inc. and their respective affiliates will not accept liability for more than replacement product or sales price refund under any circumstances.

COMPANY IDENTIFICATION

Manufactured for: DAP Canada, 475 Finchdene Square, Unit 5, Scarborough, ON, M1X 1B7

Usage Information: Call 888-DAP-TIPS or visit dap.ca & click on "Ask the Expert"

Order Information: 800-668-9397 or 416-321-1522

Fax Number: 416-321-3325

Also visit the DAP website at dap.ca