



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## DAP® ECLIPSE™ Rapid Wall Repair Patch

### PRODUCT DESCRIPTION

DAP® ECLIPSE™ Rapid Wall Patch is a patent pending, innovative drywall repair patch that is perfect for completing permanent repairs on damaged walls and ceilings and is DAP's fastest, strongest and thinnest drywall repair solution. This specially formulated, self-adhesive patch is easy to apply and mess-free allowing you to paint immediately without the need for spackling or sanding. This all-in-one, mess free solution not only provides a permanent, long-lasting repair but is also stronger than drywall itself making it perfect for areas that may see reoccurring impact, such as behind a door. It's as simple as patch, paint and finish.



PACKAGING	COLOR	UPC
4 – 2 Inch Repair Patch	Clear	7079874902
1 – 4 Inch Repair Patch	Clear	7079874904
1 – 6 Inch Repair Patch	Clear	7079874906

### KEY FEATURES & BENEFITS

- **DAP'S FASTEST, STRONGEST & THINNEST DRYWALL REPAIR SOLUTION**
- **Stronger Than Drywall Itself\***
- **Superior Impact Resistance**
- **All-In-One, Mess-Free**
- **No Spackling, Sanding or Tools Required**
- **Finish Project Faster**
- **Paint Immediately & Finish in Minutes**
- **Permanent, Long-Lasting**
- **Wont' peel or lose adhesion over time**
- **Ideal for repairing damage on drywall wall and ceiling**

\*6-inch patch is 4X Stronger and 4-inch patch is 2X Stronger than drywall itself

### SUGGESTED USES

Ideal for completing permanent repairs on damaged walls and ceilings.



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

- **ECLIPSE 2-Inch Repair Patch:** repairs damage up to 1 inch in diameter and is ideal for small repairs such as nail holes, nail pops, screw holes, anchor damage and cable cord removal damage
- **ECLIPSE 4-Inch Repair Patch:** repairs damage up to 2 inches in diameter and is ideal for medium repairs and everyday wall damaged caused by moving furniture, roughhousing or relocating towel racks or toilet paper holders
- **ECLIPSE 6-Inch Repair Patch:** repairs damage up to 3 inches in diameter and is ideal for larger repairs and specifically designed to withstand doorknob impact

## FOR BEST RESULTS

Make sure to follow the preparation instructions prior to completing the repair (prepping the drywall surface is one of the most important steps to achieving professional results). The smoother your drywall surface is prior to patching, the smoother your finished repair will be.

After removing the protective layer utilizing the pop-up tab, apply two additional thick coats of paint.

Use of a primer coat will increase paint adhesion and dry time.

Do not apply when temperatures are below 5°C.

Not for exterior use or on wet or damp surfaces. Not for use on unstable surfaces where joint movement may occur.

## APPLICATION

### 1. PREP



**Prep:** Push in any damaged or rough edges to the inside of the wall and sand drywall damage and surrounding area, smooth using fine-grit sandpaper. Using a dry or damp cloth, clean the surface to be repaired to remove any foreign material, making sure you have a smooth and clean surface. If you use a damp cloth, make sure the entire surface is dry before applying ECLIPSE wall patch.

### 2. PEEL



**Peel:** Using the easy-to-remove slit, remove the patch from the back, white carrier sheet (similar to removing a sticker) exposing the entire adhesive surface of the patch.



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224



**Place:** Holding the outer edges of the patch, position the grey center circle of the patch over the center of the damage on the wall and use your hand to completely smooth and adhere the patch to the surrounding drywall. Press firmly only on the area that the patch is in contact with the drywall. Do not push through the damaged area. Do not remove the DAP pop up tab or protective layer until after first coat of paint.



**Paint:** Paint immediately with a high-quality paint roller and interior latex paint. Paint with light pressure and copious amount of paint. The use of spackling is not necessary, and sanding is not recommended.



**Remove:** After first coat of paint is applied and surrounding drywall is dry, remove the clear protective layer by pulling the pop-up tab.



**Finish:** Paint again with two thick coats of high-quality paint using a roller and interior latex paint.. ECLIPSE can also be used for textured walls & ceilings with use of aerosol spray textures or textured paint rollers\*.

\*If using DAP Eclipse Rapid Wall Repair Patches on textured walls, skip step 4 and move directly to step 5 by removing the protective layer immediately after patching the damaged surface. Then apply texture using aerosol spray textures or textured paint rollers to match existing wall surface.



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Vehicle	Transparent Film
Application & Service Temperature	12°C and 32°C
Shelf Life	24 months
Freezing	Freeze/thaw stable 5 cycles at 0°F
Dry Time	See paint manufacturer recommendation for dry time The paint dries slower on the patch than the surrounding drywall

## CLEAN UP & STORAGE

Store patches inside in a cool, dry place away from extreme heat or cold.

## SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at [dap.com](http://dap.com) or by calling 888-DAP-TIPS.

## WARRANTY

DAP Canada, DAP Products Inc. and their respective affiliates will not accept liability for more than replacement product or sales price refund under any circumstances

## COMPANY IDENTIFICATION

**Manufactured for:** DAP Canada, 475 Finchdene Square, Unit 5, Scarborough, ON, M1X 1B7

**Usage Information:** Call 888-DAP-TIPS or visit [dap.ca](http://dap.ca) & click on “Ask the Expert”

**Order Information:** 800-668-9397 or 416-321-1522

**Fax Number:** 416-321-3325

**Also visit the DAP website at [dap.ca](http://dap.ca)**