



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## DAP® 2in1 Wall & Ceiling Spray Texture: Popcorn Water Based

### PRODUCT DESCRIPTION

**DAP® 2in1 Wall & Ceiling Spray Texture Popcorn Water Based** is an innovative technology system that allows you to tackle wall, ceiling & hard to reach areas with just one can. DAP's Aim Tech adjustable nozzle can be easily rotated upwards to spray at almost any angle achieving maximum coverage. Its ergonomic system provides professional hopper results and ultimate spray control. The aerosol can is extremely easy to use, offers a wide fan for even coverage without excessive dripping or clogging. Fast dry time of 30 minutes. Superior paintability; no priming needed and won't soften or drag. Interior/Exterior.



PACKAGING	COLOUR	SKU	UPC
567 g	White	7079870025	070798700253

### KEY FEATURES & BENEFITS

- Ideal for vertical, overhead and hard to reach areas
- Wide coverage with even spray application
- Excellent match to textured surfaces
- 30 minute paint ready time depending on temperature, humidity & application thickness
- Strong and durable
- Low odour
- Easy water clean-up



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## SUGGESTED USES

### USE FOR REPAIRING TEXTURED SURFACES:

- Drywall
- Stucco
- Plaster

## FOR BEST RESULTS

- Shake well before spraying and frequently during use
- Apply in temperatures above 5°C (40°F)
- Spray using intermittent bursts
- Dispense a quick burst on scrap material to activate product flow
- Practice applying on scrap material before use
- Store away from direct heat in temperatures ranging from 5°C to 32°C (40°F to 90°F)

## APPLICATION

### Surface Preparation

Surface must be clean, dry, structurally sound and free of all foreign material.

Make any necessary repairs to surface and ensure it is smooth and dry prior to applying spray texture.

### Product Application

1. **UNLOCK** tab by bending backwards. THIS IS A RE-LOCKING TAB AND NOT MEANT TO BE BROKEN OFF.
2. **ADJUST** nozzle upward to desired spray angle, can rotate up to 60 degrees. BE SURE TO POINT AWAY FROM FACE AND PEOPLE.
3. **SHAKE** can upside down vigorously for more than one minute after hearing mixing marble moving freely in the can. **IMPORTANT** Dispense a quick burst of material on scrap material to activate before applying to surface.
4. **SPRAY** holding can approximately 30 to 45 cm (12 to 18 inches) away from surface using intermittent bursts, sweeping across the repair in a quick, continuous motion. For superior blending, feather texture into surrounding repair area. Add coverage as needed to match texture density, by applying in layers and waiting for each layer to dry before applying another layer. If not satisfied, scrape off and reapply. **IMPORTANT** be sure that the area is well ventilated and proper safety gear is worn.
5. **PAINT:** PAINTING IS NOT REQUIRED FOR FINISHING. If painting is needed, allow texture to dry for 30 minutes prior to painting. Dry time may be longer in cooler/humid conditions or with thicker applications. Follow paint manufacturer's instructions for best results. Exterior applications and applications subject to water exposure must be sealed with a waterproof coating prior to moisture exposure-
6. **CLEAN-UP** tools and area with towel and warm water. Place nozzle in the upright position, invert can, pointing the top straight down. Spray into a disposable bag or can until no texture sprays outs. Be sure to remove any texture build up from tip/nozzle to prevent material drying on tip/nozzle.
7. **STORE**, adjust spray nozzle angle to starting position and re-lock using tab. Store container in a cool, dry place away from extreme heat or cold.



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Typical Uncured Physical Properties	
Appearance/Consistency	White textured material
Base Polymer	Acrylic Latex
Weight % Solids	45.4%
Density (lbs per gallon)	10.4
Odour	Low odour
Clean Up	Water
Shelf Life	12 months
Coverage	Up to 12 sq. ft.
Typical Application Properties	
Application Temperature Range	Best between 18°C – 26°C (65°F – 80°F)

## CLEAN UP & STORAGE

Clean up excess wet spray texture with warm water and soap. Excess dried spray texture must be cut or scraped away. Clean skin with warm water and soap. Store container in a cool, dry place away from extreme heat or cold.

## SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at [dap.ca](http://dap.ca) or by calling **888-DAP-TIPS**.

## LIMITED WARRANTY

If product fails to perform when used as directed, call 888-DAP-TIPS for replacement product or sales price refund. DAP Canada will not be responsible for incidental or consequential damages.



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## COMPANY IDENTIFICATION

**Manufactured for:** DAP Canada, 475 Finchdene Square, Unit 5, Scarborough, ON, M1X 1B7

**Usage Information:** Call 888-DAP-TIPS or visit [dap.ca](http://dap.ca) & click on "Ask the Expert"

**Order Information:** 800-668-9397 or 416-321-1522 or [CanadaOrders@DAP.com](mailto:CanadaOrders@DAP.com)

**Fax Number:** 416-321-3325

Also, visit the DAP website at [dap.ca](http://dap.ca)