



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® 2in1 Wall & Ceiling Spray Texture: Knockdown Water Based

PRODUCT DESCRIPTION

DAP® 2in1 Wall & Ceiling Knockdown Water Based is an innovative technology system that allows you to tackle wall, ceiling & hard to reach areas with just one can. DAP's Aim Tech nozzle can be easily rotated upwards to spray at almost any angle achieving maximum coverage. Its ergonomic system provides professional hopper results and ultimate spray control. The aerosol can is extremely easy to use, offers a wide fan for even coverage without excessive dripping or clogging. Proven to create a seamless blend with existing textured surfaces by adjusting the texture size to your desired finish. Fast dry time of 30 minutes. Excellent paintability; no priming needed and won't soften or drag. Interior/Exterior.



PACKAGING	COLOUR	SKU	UPC
709 g	White	7079870010	070798700109

KEY FEATURES & BENEFITS

- Ideal for vertical, overhead and hard to reach areas
- Wide coverage with even spray application
- Excellent match to textured surfaces
- 30 minute paint ready time
- Strong and durable cure
- Low odour
- Easy water clean-up
- Interior/exterior



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

SUGGESTED USES

USE FOR REPAIRING TEXTURED SURFACES:

- Drywall
- Stucco
- Plaster

FOR BEST RESULTS

- **IMPORTANT:** Shake well before and frequently during spraying
- Cover surrounding areas to protect from over spray
- Apply in temperatures between 18°C – 26°C (65°F – 80°F)
- Dispense a quick burst on scrap material to activate pressure
- Practice applying on scrap material before applying
- Spray using intermittent bursts
- Dip putty knife in water before each knockdown stroke
- Store away from direct heat in temperatures ranging from 5°C to 32°C (°40°F to 90°F)

APPLICATION

Surface Preparation

Surface must be clean, dry, structurally sound and free of all foreign material.

Make any necessary repairs to surface and ensure it is smooth and dry prior to applying spray texture.

Product Application

1. **IMPORTANT** be sure that the area is well ventilated and proper safety gear is worn. **UNLOCK** tab by bending backwards. THIS IS A RE-LOCKING TAB AND NOT MEANT TO BE BROKEN OFF.
2. **ADJUST** nozzle upward to desired spray angle, nozzle can rotate up to 60 degrees. BE SURE TO POINT AWAY FROM FACE AND PEOPLE.
3. **TWIST** nozzle to desired texture size fine, medium, or heavy.
4. **SHAKE** can upside down **vigorously** for more than one minute after hearing mixing marble moving freely in the can. **IMPORTANT** Dispense a quick burst of material on scrap materials to activate before applying to surface.
5. **SPRAY** holding can approximately 30 to 45 cm (12 to 18 inches) away from surface using intermittent bursts, sweeping across the repair in a quick, continuous motion. For superior blending, feather texture into surrounding repair area using the can. Add coverage as needed to match texture density. If not satisfied, scrape off and reapply.
6. **KNOCKDOWN:** Allow spray texture to dry: immediately for fine, 30 secs to 1 minute for medium and 1-2 minutes for heavy. Hold putty knife parallel to the wall or ceiling and lightly flatten knockdown to desired texture. **IMPORTANT** be sure to dip putty knife into water in between each knockdown.
7. **PAINT**, allow texture to dry for 30 minutes prior to painting. Dry time may be longer in cooler/humid conditions or with thicker applications. Follow paint manufacturer's instructions for best results. For exterior applications, use an exterior grade paint.
8. **CLEAN-UP** tools and area with towel and warm water.
9. **STORE:** adjust spray angle to starting position and re-lock using tab. Place nozzle in the upright position, invert can, point the top straight down. Spray onto a disposable surface until no texture sprays out. Be sure to remove any texture build up from tip/nozzle to prevent material drying on tip/nozzle.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Typical Uncured Physical Properties	
Appearance/Consistency	White textured material
Base Polymer	Acrylic Latex
Weight % Solids	55.6%
Density (lbs per gallon)	10.9
Odour	Low odour
Clean Up	Water
Shelf Life	12 months
Coverage	Fine: up to 130 sq. ft. Medium: up to 90 sq. ft. Heavy: up to 70 sq. ft.
Typical Application Properties	
Application Temperature Range	Best between 18°C – 26°C (65°F – 80°F)
Typical Cured Performance Properties	
Service Temperature Range	Above 5°C (40° F)

CLEAN UP & STORAGE

Wet material can be cleaned up with soap and water. Excess dried material must be scraped or sanded away. Store away from direct heat in temperatures ranging from 5°C to 32°C (40°F to 90°F).

SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.ca or by calling **888-DAP-TIPS**.

LIMITED WARRANTY

Limited Warranty: If product fails to perform when used as directed, call 888-DAP-TIPS for replacement product or sales price refund. DAP Canada will not be responsible for incidental or consequential damages.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

COMPANY IDENTIFICATION

Manufactured for: DAP Canada, 475 Finchdene Square, Unit 5, Scarborough, ON, M1X 1B7

Usage Information: Call 888-DAP-TIPS or visit dap.ca & click on "Ask the Expert"

Order Information: 800-668-9397 or 416-321-1522 or CanadaOrders@DAP.com

Fax Number: 416-321-3325

Also, visit the DAP website at dap.ca